


Depot

**Designed for industrial applications.
Simultaneous charging.
Compact and robust design.**



Actualización de Hardware – Próximamente

Depot Dispenser



REFERENCE		NBDI200H NBDI200U	NBDI400H NBDI400U
DC OUTPUT	Maximum continuous current [A]	Current limited by the selected connector rating [Table 1]	
	Peak current [A] ^[1]	500	
	Voltage range [V]	150 – 1000	
	Available connectors	CCS-1, CCS-2 and NACS	
GENERAL	Interface	Status LED indicator	
		E-stop pushbutton	
		Stop charging button	
	Protections	Insulation Monitoring Device	
	Cable length [m/ft]	5.5 / 13.1; 7.6 / 25	
	Protection ratings	NEMA 3R IP54 IK10 (IK08 for ventilation grilles)	
	Enclosure / Pedestal color	White (RAL 9016) / Grey (RAL 7016)	
	Customization ^[2]	Enclosure (Color/Vinyl) / Logo	
	Operation temperature range [°C/°F]	Standard: -25 to 50 / -13 to 122 Optional: -30 to 50 / -22 to 122	
	Relative humidity	From 4% to 95%	
	Maximum altitude above sea level [m/ft]	2000 / 6561 without derating (Max: 3000 / 9842)	
	Charging protocols	ISO 15118 and DIN 70121	
	Communication protocols	OCPP 1.6J, OCPP 2.0.1 ^[2] , API Rest ^[3]	
	Dimensions (WxDxH) [mm/ft]	600 x 322 x 800 (1450 with pedestal) / 1.97 x 1.06 x 2.62 (4.76 with pedestal)	
	Weight (kg/lb)	125 / 276	
	Regulation	IEC 61851-1, IEC 61851-23, IEC 61851-24, IEC 61851-21-2 UL 2202, NEC 625, FCC Part 15 Class A	

NOTES

[1] Consult with Power Electronics for more information about the connector overload capability.

[2] Consult availability with Power Electronics.

[3] Consult with Power Electronics for further information.

[Table 1] Select connector current rating in the table below:

CCS1	200 A	375 A
CCS2	200 A	375 A
NACS	-	375 A