


NB Wall

UL

Multiple connection options
Dynamic power control
Customizable design





Model	BASIC	ADVANCED	PROFESSIONAL
AC input [V]	208 / 240 (L1, L2, PE)		
Maximum output power per connector [kW]	6.7 / 7.7		
Energy measurement	Internal energy measurement		
	-	-	Revenue meter
Communications	Wifi		
	-	-	3G / 4G connectivity
	Ethernet		
	OCPP 1.6		
Authentication	RFID card reader		
Protections	-	CCID	CCID
	-	MCB	MCB
External enclosure	NEMA 3R		
	White colour (RAL 9016 - microtexture painting)		
	C4 anti-corrosion protection ^[1]		
Glass colour	Black		
Operating temperature	From -13°F to 122°F		
Relative humidity	4% - 95%		
Interface	Status indicator		
Dimensions (W x D x H) [mm]	Frame 1: 1.01 x 0.65 x 1.01		
	Frame 2: 1.01 x 0.65 x 2.46		
Cable input	Frame 1: Bottom input		
	Frame 2: Bottom and rear input		
Regulation	UL 2594, FCC Part 15 Class B, NEC 625		

	FRAME	MODEL	REFERENCE	TYPE OF CONNECTOR
STANDARD MODELS	FRAME 1	BASIC	NBWUB23	1 x AC Type 1 (Plug - 13.1 ft spiral)
		ADVANCED	NBWUA23	1 x AC Type 1 (Plug - 13.1 ft spiral)
		PROFESSIONAL	NBWUP23	1 x AC Type 1 (Plug - 13.1 ft spiral)
	FRAME 2	BASIC	NBWUB28	2 x AC Type 1 (Plug - 13.1 ft spiral)
		ADVANCED	NBWUA28	2 x AC Type 1 (Plug - 13.1 ft spiral)
		PROFESSIONAL	NBWUP28	2 x AC Type 1 (Plug - 13.1 ft spiral)

AVAILABLE OPTIONS	Cable lenght Normally is 13.1 ft of spiral, but you could also have 18 ft of straight cable	Dynamic power control One option < 300 A
-------------------	---	--